

## WHICH WHEEL BALANCERS ARE RIGHT FOR YOUR SHOP?

KEY: Services most tires/wheels Services some tires/wheels Not recommended \*Requires optional adapter for service













investment:	\$ \$ \$	\$ \$	\$ \$	\$	\$ \$ \$	\$ \$ F
features:	<ul> <li>Laser pointer indicates exact positioning for weights</li> <li>Guided balancing procedure on display</li> <li>Fully automatic wheel dimension entry</li> <li>Auto stop on top and auto indexing</li> <li>Auto start hood feature</li> <li>7 piece collet set standard</li> <li>Small light truck cone standard</li> </ul>	<ul> <li>Laser line indicates positioning for weights</li> <li>3D data entry with digital caliper and width caliper</li> <li>Guided balancing procedure on display</li> <li>Auto stop on top and auto indexing</li> <li>Auto start hood feature</li> <li>7 piece collet set standard</li> <li>Small light truck cone standard</li> </ul>	<ul> <li>2D data entry with data set arm</li> <li>Side storage board standard</li> <li>Split weight / hidden weight mode</li> <li>Positioning pedal</li> <li>Auto stop on top and auto indexing</li> <li>7 piece collet set standard</li> <li>Small light truck cone standard</li> </ul>	<ul> <li>Automatically measures distance and diameter with digital caliper</li> <li>Heavy duty shaft and large offset</li> <li>Large digital display</li> <li>Has a very small shop footprint</li> <li>Auto stop on top</li> <li>Passenger tire and light truck cone kits standard</li> </ul>	<ul> <li>Microprocessor provides self-calibration and self-diagnostics</li> <li>Single spin with low rotation speed provides all values</li> <li>Specific balancing programs for static, dynamic and ALU wheels</li> <li>Air lift with capacity of 441 lbs</li> <li>Auto stop on top and auto indexing</li> </ul>	<ul> <li>2D data entry with LED display</li> <li>Microprocessor controlled self-calibration and self diagnosis</li> <li>Programs for static, dynamic and ALU wheels</li> <li>Quick nut locking</li> <li>Passenger and HD adapters</li> <li>Air lift with capacity of 441 lbs</li> <li>Auto stop on top and auto indexing</li> <li>EASY STATIC™ mode - balance with one quick data entry</li> <li>Break at weight position</li> <li>Split weight / hidden weight feature in passenger mode</li> </ul>
voltage required:	110 volt	110 volt	110 volt	110 volt	110 volt	110 volt
services:						
max tire diameter:	44"	44"	44"	35.4"	51"	51"
max wheel diameter:	30"	30"	30"	26"	30"	30"
max tire width:	22"	22"	22"	22"	22"	22"
	R180 Pro 3D Auto	R155 Pro 3D	R148 Pro 2D	R138 Shop 2D	R544 Plus Truck 3D	R540 RTLD Truck 2D
	<b>E</b>	B W	E as			