



WHICH TIRE CHANGERS ARE RIGHT FOR YOUR SHOP?

KEY: ■ Services most tires/wheels ■ Services some tires/wheels ■ Not recommended ^o Requires adapter for motorcycle service *May need optional adapters



	R1200 Leverless Pro	R1150 Leverless	R145DR Auto Tiltback	R247D.CLI Swing Arm	R146R / R146RPS+ Swingarm Pro	R140i Swingarm Shop	R501 PLUS Speedchanger HD	R560 Mobile HD	R511 Commercial HD	R541 Commercial HD	R573 Extreme HD
max tire width:	15"	15"	17"	15"	15"	12"	21"	37.4"	36.4"	51"	69"
max wheel diameter:	30"	30"	26"	30"	26"	22"	27"	27"	27"	Up To 56" *	Up To 60" *
max tire diameter:	45"	45"	45"	45"	46"	40.5"	51"	51"	64"	90.5"	106"
specialty rims:	●	●	●	●	● *	● *					
19.5" rims:	●	●	●	●			●	●	●	●	●
services:											
best for:	specialty rims/tires ^o	safety and process	specialty rims/tires ^o	specialty rims/tires ^o	high performance/volume ^o	quality and low price ^o	speed and productivity	mobile and small shops	versatility	larger applications	universal - extreme dimensions
features:	<ul style="list-style-type: none"> Automatic leverless mounting and demounting - no tire lever required Hub mounted, synchronized dual bead breaking rollers 220-volt motor with true variable control speed, pedal-operated Pedal-operated inflation with gauge and balancing valve Three-position pedestal Pneumatic tire lift Integrated helper arm 	<ul style="list-style-type: none"> Leverless mounting and demounting - no tire lever required 220-volt motor with true variable control speed, pedal-operated Pedal-operated inflation with gauge and balancing valve Three-position expandable base 	<ul style="list-style-type: none"> Hand controlled, double-acting bead breaker works on low-profile and large steel or alloy rims 220-volt motor with true variable control speed, pedal-operated Prevents rim damage Pneumatically tilting column ensures peak rigidity to prevent rim damage 	<ul style="list-style-type: none"> Hand controlled, double-acting bead breaker works on low-profile, large steel or alloy rims Quick locking wheel centering system eliminates wheel damage due to improper clamping 220v drive motor with true variable control speed provides needed torque 	<ul style="list-style-type: none"> Hand controlled bead breaker Extra-height speedchanger 110-volt drive motor provides torque All the features of the R146, plus a top bead-pressing helper arm and pneumatic wheel lift Air-powered, non-electric units available 	<ul style="list-style-type: none"> Top quality at an entry-level price 110-volt single-speed motor provides excellent torque Optional helper arm available 	<ul style="list-style-type: none"> Dismounts and mounts truck tires in 30 seconds Adjustable arm position Four rollers positioned on both sides of the wheel in diametrically opposite positions Ergonomic (back saving) design Includes standard clamp protection kit for alloy rims 	<ul style="list-style-type: none"> Hydraulic clamping and up/down movement Standard finger adapter for tube tires Includes standard clamp protection kit for alloy rims 	<ul style="list-style-type: none"> Rotational control on portable wired stand Cable control unit Quick manual rotation of tool head Ideal for agricultural and implement application Includes standard clamp protection kit for alloy rims 	<ul style="list-style-type: none"> Leverless operation, single carriage Rotational control on portable wired stand Cable control unit Quick manual rotation of tool head Double ratcheting locking arm Ideal for agricultural and implement applications Includes standard clamp protection kit for alloy rims 	<ul style="list-style-type: none"> Console cable control unit with a metal sheath and rotational control on portable wired stand Double speed table rotation with quick locking manual rotation tool B530800 long bead lifting lever VSG108A25 / clamp for earthmoving wheels Includes clamp kit to protect alloy rims Available wireless Bluetooth^o control
investment:	\$\$\$\$\$	\$\$\$\$	\$\$\$	\$\$\$	\$\$	\$	\$\$\$\$\$	\$\$\$\$	\$\$\$\$\$	\$\$\$\$\$	\$\$\$\$\$

Learn more about our wheel service equipment at rotarywheelservice.com.