

Reliable lift systems for independent repair shops, car dealerships, bodyshops, home enthusiasts, and heavy-duty truck facilities.

LIGHT DUTY TWO POST LIFT 10,000 lbs. Capacity

## **FEATURES:**


Symmetrical column design

Spot-Rite™ 3-stage front arm design - spot vehicles asymmetrically or symmetrically

- Top mounted Direct-Pull lifting technology
- Cylinder rod concealed inside carriage
- Adjustable width options
- Single point lock release
- Powder coated finish
- Includes adapter storage bracket
- **ALI Certified**

**INCLUDES LOW-PROFILE THREADED ADAPTERS AND (4 each) ADAPTER EXTENSIONS AT** 





**Asymmetric** Vehicle Placement

Symmetric Vehicle Placement

FWD I10N400MBL

## DRWARDLET

Spot-Rite™3-Stage

**Front Arm Design** 

both symmetrically and

asymmetrically. Position the

vehicle doors in front of or

behind the lift columns to

andallow easy technician

prevent door damage

Printed in the U.S.A.

access!

accommodates vehicle spotting

996 Industrial Drive


Phone: 800.423.1722 Fax: 812.273.7329



Madison, IN 47250



Unless otherwise indicated, Forward Lift, Vehicle Service Group<sup>SM</sup>, Dover and all other trademarks are property of Dover Corporation and its affiliates.



SPECIFICATIONS

Capacity

Maximum rise

Overall Height

Overall Width

Drive through clearance

Overhead switch height

Front reach (Min/Max)

Min/Max adapter height

Width inside column

Voltage/ Amps

Motor/Phase

I10N400MBL/RD\*

10,000 lbs. (4535kg)

143" (3632mm)

137-5/8" (3496mm)

208V/230V, 17 amps

1ph/2HP/60Hz

144" (3658mm)

76 -1/4" (1937mm) w/5" extension

23" / 44-3/8" (584mm/1127mm)

3-3/4" (95mm) w/o adapter extension

8-3/4" (222mm) w/ 5" adapter extension

109" or optional 115" (2769mm/2921mm)

131" or optional 137" (3327mm/4380mm)

99" (2515mm) or optional 105" (2667mm)

Specifications subject to change without notice or liability.

Rear reach (Min/Max) 36" / 58" (914mm/1473mm)

